# TECHNICAL DATA SHEET



TD100-10-2018

# Product Number: 100

## Intumescent Fire & Smoke Seals

## **Description:**

Plastic intumescent fire and smoke seals. Can be supplied with or without smoke seals and in a range of sizes and in two lengths (1050mm and 2100mm). They are fitted with self-adhesive backing to adhere into the rebate. Smoke seals can be either brush or rubber. NB: as smoke can kill before a fire, it is always best to fit intumescent seals with smoke seals. Please also see Product 101 Push-Fit Seals

#### Use:

Used for fitting to doors, door frames and windows. Once fitted the plastic facing of the seals can be painted, although the brush or rubber smoke seal must NOT be painted.

### Ordering references:

REF	SIZE	PROTECTION
IS13	10mm x 3mm	30 minutes
IS13/S	10mm x 3mm with brush	30 minutes
IS14	10mm x 4mm	30 minutes
IS14/S	10mm x 4mm with brush	30 minutes
IS15	15mm x 3mm	60 minutes
IS15/S	15mm x 3mm with brush	60 minutes
IS154	15mm x 4mm	60 minutes
IS154/S	15mm x 4mm with brush	60 minutes
IS24	20mm x 4mm	60 minutes
IS24/S	20mm x 4mm with brush	60 minutes

All of the above are available in brown or white and 1050mm or 2100mm lengths – please state when ordering.

All of the above are available with 5mm, 7mm or 10mm brush with or without fin. Standard brush colours are black, brown, grey or white. Please state when ordering.

12mm or 15mm brushes are available only in white or grey – there is an added charge for these.

If you require rubber seals there is an added charge. The only types that can be used in the IS Range are the angled and straight types.

Angled – 6mm or 9mm

Straight – 5mm, 7mm or 10mm

Important – 1-1½mm of the brush or rubber seal is held within the holder. Brush with fin is always ½mm higher than regular brush. Make allowance for this when specifying.